
55102281 HANSASIGNATUR Hybrid - Washbasin faucet, 3 V


Discontinued

EAN: 4015474278035
static.hansa.com/55102281



- Washbasin
- Hybrid, Battery-operated
- Deck mounted
- Chrome
- Swivel spout, Pull-out model
- Temperature control handle
- Push pop-up waste without draw-rod
- Limitation option for maximum temperature and flow-rate, Adjustable hot water stop (included, retrofittable)
- Thermostatic cartridge for automatic temperature control, Non-return valve(s), ø 40 mm ceramic cartridge for flow and temperature control
- Flexible inlet pipes
- Software settings adjustable via magnetic key, Waterways without nickel coating





© 2024 Hansa Armaturen GmbH - www.hansa.com - 22.09.2023

Technical data

Flow properties

Flow-rate at 3 bar	**6.0 l/min**

Technical properties

DN-size (nominal dimension)	**DN15**
Hot water supply	**max. +70°C**
Working pressure	**1-10 bar**
Connection size	**G3/8**
Projection	**168 mm**
Backflow prevention (EN1717)	**EB**
Material	**Brass**

Software settings

Automatic flush	**off (off/12/24/48/72 h)**
Automatic flush period	**30 s (10/30/60/120/180/240/300/600 s)**

Electronic properties

Battery	**AA 1.5 V Lithium x 2**


Regulations


EU Directives	**CE EMC Directive 2014/30/EU , RoHS Directive 2011/65/EU**
EN standard	**EN 15091, ETSI EN 301 489-1 V1.9.2 , ETSI EN 300 328 v2.2.2 , EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011+AC:2012 , EN 60335-1:2012+A11+A13+A1+A14+A2+A15:2021, Part 19.11.4**
Protection class	**IP 55**

Approvals and Declarations


UN38.3	**1118120077**

GERMAN DESIGN AWARD SPECIAL 2016






Spare parts



SP55102281

	Name	Code
1	Lever	59914340
2	Symbol plug	59914341
3	Covering cap Discontinued	59914342
4	Tightening nut, M42x1,5, SW 38	59914128
5	Cartridge, 4.0 Classic	59914129
6	O-ring, 53.64x2.62	59914369
7	Supporting plate	59910008
8	Fixing screw, M6x65 Discontinued	59914259
9	Fixing plate with a nut	59914344
10	Rapid pop-up waste	59913988
11	Pull-out spout, (-2018)	59914346
11	Pull-out spout, (2018-)	59914711
12	Aerator and key, M18.5x1	59914350
13	Hose, L=1500, G1/2-M15x1	59914345
14	Sensor, 3 V	59914347
15	Counterbalance	59914039
16	Control unit, 3 V /RF Discontinued	59914623
17	Battery, 1.5 V AA Lithium	59914136
18	Solenoid valve complete, 3 V	59914125
19	Membrane for solenoid valve	1006500V
19	Membrane Discontinued	59914126
20	Thermostatic cartridge, 3.4	59914114
21	Temperature control handle	59914134
22	Non-return valve, DN15	59914250

© 2024 Hansa Armaturen GmbH - www.hansa.com - 22.09.2023



SP55102281J

	Name	Code
1	Lever	59914340
2	Symbol plug	59914341
3	Covering cap Discontinued	59914342
4	Tightening nut, M42x1,5, SW 38	59914128
5	Cartridge, 4.0 Classic	59914129
6	O-ring, 53.64x2.62	59914369
7	Supporting plate	59910008
8	Fixing screw, M6x65 Discontinued	59914259
9	Fixing plate with a nut	59914344
10	Rapid pop-up waste	59913988
11	Sealing kit, 15x10x1	59902927
12	Litter filters	59914085
13	Non-return valve, DN8	59914030
14	Handle	59914171
15	Thermostatic cartridge, 2.7	59913823
16	Membrane for solenoid valve	1006500V
16	Membrane Discontinued	59914126
17	Solenoid valve complete, 3 V	59914125
18	Counterbalance	59914039
19	Battery, 1.5 V AA Lithium	59914136
20	Control unit, 3 V Discontinued	59914348
21	Sensor, 3 V	59914347
22	Hose, L=1500, G1/2-M15x1	59914345
23	Aerator and key, M18.5x1	59914350
24	Pull-out spout, (-2018)	59914346
N.I.	Flexible pipe, L=430, G3/8-M8x1	59913964
N.I.	Key, 38 mm	59914176
N.I.	Socket wrench, 9 mm	59914181

© 2024 Hansa Armaturen GmbH - www.hansa.com - 22.09.2023