
# 55112201 HANSASIGNATUR Hybrid - Washbasin faucet, 3 V


Discontinued

EAN: 4015474277878
static.hansa.com/55112201



- Washbasin
- Hybrid, Battery-operated, Bidetta
- Deck mounted
- Chrome
- Swivel spout
- Temperature control handle
- Push pop-up waste without draw-rod
- Hand shower, Shower holder, Shower hose (1500 mm)
- Remote-operated Smart Bidetta
- Limitation option for maximum temperature and flow-rate, Adjustable hot water stop (included, retrofittable)
- Thermostatic cartridge for automatic temperature control, Non-return valve(s), Litter filter(s), ø 40 mm ceramic cartridge for flow and temperature control
- External control unit
- Flexible inlet pipes
- Software settings adjustable via magnetic key, Waterways without nickel coating







© 2024 Hansa Armaturen GmbH - www.hansa.com - 22.09.2023

## Technical data

### Flow properties

| | |
|---|---|
| Flow-rate at 3 bar | **6.0 / 6.0 l/min** |




### Technical properties

| | |
|---|---|
| DN-size (nominal dimension) | **DN15** |
| Hot water supply | **max. +70°C** |
| Working pressure | **1-10 bar** |
| Connection size | **G3/8** |
| Projection | **168 mm** |
| Backflow prevention (EN1717) | **EB** |
| Material | **Brass** |

### Software settings

| | |
|---|---|
| Automatic flush | **off (off/12/24/48/72 h)** |
| Automatic flush period | **30 s (10/30/60/120/180/240/300/600 s)** |
| Max. flow period | **6 s (4/6/8/10/20/60 s)** |

### Electronic properties


| | |
|---|---|
| Battery | **AA 1.5 V Lithium x 2, CR 2450 3 V** |

### Regulations


| | |
|---|---|
| EU Directives | **CE EMC Directive 2014/30/EU , RoHS Directive 2011/65/EU** |
| EN standard | **EN 15091, ETSI EN 301 489-1 V1.9.2 , ETSI EN 300 328 v2.2.2 , EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011+AC:2012 , EN 60335-1:2012+A11+A13+A1+A14+A2+A15:2021, Part 19.11.4** |
| Protection class | **IP 55** |

### Approvals and Declarations

| | |
|---|---|
| UN38.3 | **UN38-3 Energizer L91** |



## Spare parts




### SP55112201

| | Name | Code |
|---|---|---|
| 1 | Lever | 59914340 |
| 2 | Symbol plug | 59914341 |
| 3 | Covering cap Discontinued | 59914342 |
| 4 | Tightening nut, M42x1,5, SW 38 | 59914128 |
| 5 | Cartridge, 4.0 Classic | 59914129 |
| 6 | O-ring, 53.64x2.62 | 59914369 |
| 7 | Supporting plate | 59910008 |
| 8 | Fixing screw, M6x65 Discontinued | 59914259 |
| 9 | Fixing plate with a nut | 59914344 |
| 10 | Rapid pop-up waste | 59913988 |
| 11 | Spout | 59914343 |
| 12 | Aerator and key, M18.5x1 | 59914350 |
| 13 | Sensor, 3 V | 59914347 |
| 14 | Battery, CR2450 3 V Lithium | 59914137 |
| 15 | Control unit, 3 V /RF Discontinued | 59914623 |
| 16 | Battery, 1.5 V AA Lithium | 59914136 |
| 17 | Solenoid valve complete, 3 V | 59914125 |
| 18 | Membrane for solenoid valve | 1006500V |
| 18 | Membrane Discontinued | 59914126 |
| 19 | Thermostatic cartridge, 3.4 | 59914114 |
| 20 | Temperature control handle | 59914134 |
| 21 | Non-return valve, DN15 | 59914250 |

© 2024 Hansa Armaturen GmbH - www.hansa.com - 22.09.2023